



## 3MP Dome IR20 IP Camera SCALIRDNSE200



Model NO.	SCALIRDNSE200
<b>CAMERA</b>	
Image Sensor	IMX323
Main Processor	HI3518EV200
Resolution	1080P
Effective Pixels	1920(H)*1080(V)
Compression	H.264/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	3MP
<b>NIGHT VISION</b>	
Infrared LED	14μ x 18PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
<b>NETWORK</b>	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP, RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
WIFI	N/A
Video Delay	0.3S (Within the Lan)

<b>Model NO.</b>	<b>SCALIRDNSE200</b>
Main Stream 1	1920*1080@15fps
Main Stream 2	/
Main Stream 3	/
Sub Stream 1	720*480@15fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@15fps
IE Browser	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
<b>CAMERA FEATURES</b>	
Day/Night	Color/ B&W (IR-CUT )
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern	/
Defog Mode	Support
ROI	Support
BLC	Support
HDR	/
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands
<b>GENERAL</b>	
Housing	Metal
Anti-cut Bracket	NO
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	∅ 94.5 x 76(H) mm
Weight	450g

\*Due to product enhancement, Sin Chew Alarm reserved the right to change/modify specifications without prior notice.